



Lincat *Specialist*

PRODUCT OPTIONS AND ACCESSORIES

- TR54 Wire Cooking Basket

UK Meet the game-changer for professional kitchens everywhere—the commercial air fryer designed to deliver maximum crunch, zero oil, and healthier profits. Built with true commercial power but without the premium price tag.

PRODUCT FEATURES

- Air0 enables operators to serve fried-style food in locations where traditional equipment hasn't been practical.
- Zero added oil. Zero hassle. Zero compromise. A true plug-and-play unit running from a standard 13A connection—no extraction, hard wiring, water connection or specialist install required.
- Eliminates oil handling, reducing mess and associated safety risks.
- Delivers comparable performance to a conventional tabletop fryer, with consistent results and no variability from oil degradation or operator input.
- Supports cook-on-demand service and includes an eco mode that can reduce energy consumption by up to 32% during quieter periods.
- Suited to a wide range of operators—especially those who couldn't justify frying before. Ideal for pubs, cafés, grab-and-go, kiosks, leisure, and sectors including retail, forecourts, education, healthcare and contract catering.
- Uses high-velocity hot air circulation to achieve consistently crispy, golden results with significantly less fat and fewer calories. Independent lab testing shows up to 62% less fat in fries and 28% fewer calories compared to deep fat frying.
- Supports sustainability goals with 98% recyclable components, zero oil waste, and reduced energy use through fast start-up and efficient operation.
- Intuitive touchscreen controls with an icon-driven interface minimise training and remove language barriers.

A/A FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Product Width	528 mm
Product Depth	474 mm
Product Height	619 mm
Product Dimensions (WxDxH) (mm)	528 Millimeter X 474 Millimeter X 619 Millimeter
Product Weight	57 kg
Product Clearance Required: Top	50 mm
Product Clearance Required: Back	50 mm
Product Clearance Required: Left Side	50 mm

PRODUCT CERTIFICATION ICONS



ENERGY SPECIFICATIONS

Primary Energy Type	Electric
Electrical Volts	230V

bidding specifications

TECHNICAL DRAWING

Technical Pictures

